

## 型號性能表

## SELECTION GUIDE

型號 TYPE	壓力 Kg/cm <sup>2</sup>	轉速 1450RPM						轉速 1750RPM					
		黏度 20CP		黏度 100CP		黏度 500CP		黏度 20CP		黏度 100CP		黏度 500CP	
		流量 L/min	馬力 HP	流量 L/min	馬力 HP	流量 L/min	馬力 HP	流量 L/min	馬力 HP	流量 L/min	馬力 HP	流量 L/min	馬力 HP
CT1905	4	249.7	6.2	257.4	8.7	261.9	13.1	305.2	7.7	312.9	11.0	317.4	16.6
	8	231.2	8.7	246.6	11.3	255.6	15.6	286.7	10.8	302.1	14.1	311.1	19.7
	12	212.7	11.2	235.7	13.8	249.2	18.2	268.2	13.9	291.2	17.2	304.7	22.7
	NPSH(M)	1.5		1.7		2.3		1.6		1.8		2.4	
CT1908	4	363.7	7.7	375.8	10.5	382.9	15.3	445.0	9.6	457.1	13.2	464.2	19.3
	8	334.4	11.4	358.7	14.2	372.9	19.0	415.7	14.1	440.0	17.7	454.2	23.8
	12	305.1	15.1	341.6	18.0	362.9	22.8	386.4	18.6	422.9	22.2	444.2	28.4
	NPSH(M)	1.6		1.9		2.5		1.7		1.9		2.6	
CT1911	4	486.1	9.3	503.4	12.3	513.6	17.4	595.3	11.5	612.6	15.4	622.8	21.9
	8	444.5	14.3	479.1	17.3	499.3	22.4	553.7	17.6	588.3	21.4	608.5	28.0
	12	402.8	19.3	454.7	22.3	485.1	27.4	512.0	23.6	563.9	27.5	594.3	34.1
	NPSH(M)	1.7		2.0		2.6		1.8		2.1		2.8	
CT1916	4	720.1	12.1	748.0	15.4	764.3	21.1	883.0	15.0	910.9	19.3	927.2	26.5
	8	652.8	19.7	708.7	22.9	741.3	28.6	815.7	24.1	871.6	28.3	904.2	35.6
	12	585.5	27.2	669.3	30.5	718.3	36.1	748.4	33.1	832.2	37.4	881.2	44.6
	NPSH(M)	2.0		2.3		3.1		2.1		2.5		3.4	
CT2507	4	671.8	13.8	686.7	18.7	695.4	27.2	818.2	17.1	833.1	23.5	841.8	34.5
	8	636.0	20.5	665.7	25.4	683.1	34.0	782.4	25.3	812.1	31.7	829.5	42.6
	12	600.2	27.2	644.8	32.2	670.9	40.7	746.6	33.4	791.2	39.8	817.3	50.8
	NPSH(M)	1.6		1.8		2.4		1.6		1.9		2.5	
CT2511	4	1041.2	18.3	1066.4	23.8	1081.2	33.2	1269.2	22.6	1294.4	29.7	1309.2	41.8
	8	980.3	28.8	1030.9	34.3	1060.4	43.7	1208.3	35.3	1258.9	42.4	1288.4	54.5
	12	919.5	39.3	995.3	44.8	1039.6	54.2	1147.5	48.0	1223.3	55.1	1267.6	67.2
	NPSH(M)	1.7		2.0		2.7		1.8		2.1		2.8	
CT2514	4	1334.4	21.7	1368.6	27.6	1388.5	37.5	1627.5	26.9	1661.7	34.4	1681.6	47.2
	8	1252.2	35.2	1320.5	41.1	1360.4	51.0	1545.3	43.2	1613.6	50.7	1653.5	63.5
	12	1169.9	48.7	1272.4	54.6	1332.3	64.5	1463.0	59.5	1565.5	67.0	1625.4	79.8
	NPSH(M)	1.9		2.2		2.9		2.0		2.3		3.2	
CT2522	4	2064.3	30.1	2122.3	36.6	2156.2	47.6	2520.3	37.0	2578.3	45.3	2612.2	59.5
	8	1924.5	51.1	2040.6	57.6	2108.4	68.6	2380.5	62.4	2496.6	70.7	2564.4	84.9
	12	1784.8	72.1	1958.8	78.6	2060.6	89.6	2240.8	87.8	2414.8	96.0	2516.6	110.2
	NPSH(M)	2.3		2.7		3.7		2.6		3.0		4.2	
CT3310	4	1803.0	31.6	1834.7	41.4	1853.2	58.0	2191.8	39.3	2223.5	51.8	2242.0	73.2
	8	1726.9	49.6	1790.1	59.3	1827.1	76.0	2115.7	60.9	2178.9	73.4	2215.9	94.8
	12	1650.7	67.5	1745.6	77.2	1801.1	93.9	2039.5	82.5	2134.4	95.0	2189.9	116.4
	NPSH(M)	1.7		1.9		2.6		1.8		2.0		2.7	
CT3315	4	2694.9	41.9	2746.3	52.6	2776.4	70.8	3278.1	51.8	3329.5	65.5	3359.6	88.9
	8	2571.0	68.8	2673.9	79.5	2734.1	97.7	3154.2	84.2	3257.1	97.9	3317.3	121.4
	12	2447.1	95.6	2601.4	106.3	2691.7	124.6	3030.3	116.6	3184.6	130.3	3274.9	153.8
	NPSH(M)	1.9		2.2		2.9		2.0		2.4		3.2	
CT3320	4	3584.9	51.9	3657.5	63.3	3700.0	82.7	4362.8	63.9	4435.4	78.5	4477.9	103.5
	8	3409.9	87.7	3555.2	99.1	3640.2	118.6	4187.8	107.1	4333.1	121.8	4418.1	146.8
	12	3234.9	123.6	3452.8	134.9	3580.3	154.4	4012.8	150.4	4230.7	165.0	4358.2	190.0
	NPSH(M)	2.1		2.5		3.4		2.4		2.8		3.9	
CT3325	4	4470.7	61.7	4565.7	73.6	4621.2	94.1	5443.0	75.7	5538.0	91.1	5593.5	117.4
	8	4242.0	106.5	4431.9	118.4	4543.0	138.9	5214.3	129.8	5404.2	145.2	5515.3	171.5
	12	4013.3	151.3	4298.2	163.2	4464.8	183.7	4985.6	183.9	5270.5	199.2	5437.1	225.6
	NPSH(M)	2.5		2.9		4.0		2.8		3.3		4.7	
CT3330	4	5354.4	71.3	5472.6	83.8	5541.7	105.1	6521.1	87.4	6639.3	103.5	6708.4	130.9
	8	5069.7	125.1	5306.1	137.5	5444.3	158.9	6236.4	152.3	6472.8	168.3	6611.0	195.8
	12	4785.1	178.8	5139.6	191.3	5347.0	212.6	5951.8	217.2	6306.3	233.2	6513.7	260.6
	NPSH(M)	2.8		3.3		4.7		3.4		4.0		5.7	
CT4312	4	4140.1	66.1	4198.9	84.1	4233.4	114.8	5026.0	81.8	5084.8	104.9	5119.3	144.4
	8	3998.3	106.9	4116.0	124.9	4184.9	155.6	4884.2	131.0	5001.9	154.1	5070.8	193.6
	12	3856.5	147.8	4033.1	165.7	4136.4	196.5	4742.4	180.3	4919.0	203.4	5022.3	242.9
	NPSH(M)	1.8		2.1		2.8		1.9		2.2		3.0	
CT4315	4	5119.4	77.1	5195.5	95.9	5240.0	128.2	6216.5	95.1	6292.6	119.3	6337.1	160.7
	8	4936.2	127.6	5088.4	146.5	5177.3	178.7	6033.3	156.1	6185.5	180.3	6274.4	221.8
	12	4753.0	178.2	4981.2	197.0	5114.7	229.3	5850.1	217.1	6078.3	241.3	6211.8	282.8
	NPSH(M)	1.9		2.2		3.0		2.1		2.4		3.3	
CT4318	4	6161.0	88.6	6256.1	108.2	6311.8	141.8	7483.1	109.1	7578.2	134.3	7633.9	177.5
	8	5931.8	149.5	6122.1	169.1	6233.4	202.7	7253.9	182.6	7444.2	207.8	7555.5	251
	12	5702.6	210.4	5988.0	230.1	6155.0	263.7	7024.7	256.1	7310.1	281.4	7477.1	324.5
	NPSH(M)	2.1		2.4		3.3		2.3		2.7		3.7	
CT4325	4	8174.3	110.5	8308.3	131.4	8386.7	167.2	9932.3	135.6	10066.3	162.5	10144.7	208.5
	8	7851.7	191.5	8119.6	212.4	8276.3	248.2	9609.7	233.4	9877.6	260.3	10034.3	306.3
	12	7529.0	272.5	7930.9	293.4	8166.0	329.2	9287.0	331.1	9688.9	358.0	9924.0	404.0
	NPSH(M)	2.5		2.9		4.0		2.8		3.3		4.7	
CT4331	4	10198.9	132.2	10373.6	154.2	10475.8	191.8	12396.1	162.0	12570.8	190.2	12673.0	238.6
	8	9778.0	255.4	10127.5	255.4	10331.9	293.0	11975.2	284.2	12324.7	312.4	12529.1	360.7
	12	9357.0	334.7	9881.3	356.7	10187.9	394.3	11554.2	406.3	12078.5	434.6	12385.1	482.9
	NPSH(M)	2.9		3.4		4.8		3.5		4.2		6.0	
CT4337	4	12272.6	154.3	12491.2	177.2	12619.1	216.4	14920.7	188.7	15139.3	218.2	15267.2	268.6
	8	11746.1	276.3	12183.3	299.2	12439.0	338.4	14394.2	336.0	14831.4	365.4	15087.1	415.8
	12	11219.5	398.3	11875.4	421.2	12258.9	460.4	13867.6	483.2	14523.5	512.7	14907.0	563.0
	NPSH(M)	3.5		4.2		6.0		4.4		5.3		7.9	

### 注意事項 Note :

本型錄產品規格因產品改良而有所變更時，恕不另行通知，訂購時請先確認。

Because we are constantly working to improve performance and upgrade our products, specifications and diagrammatic representation in this catalog may change without notice.